



CPLG SIZE	AH	U	EU	V	W	X	Z
3	2.750	1.125	0.875	0.375	0.750	0.250	2.750
7	4.500	1.625	1.125	0.375	0.750	0.375	3.875
10	4.500	2.125	1.750	0.375	0.750	0.500	3.875
11	5.000	2.375	2.000	0.375	0.750	0.625	3.875
12	5.000	2.625	2.250	0.375	0.750	0.625	3.875
13	7.000	2.875	2.375	0.500	1.000	0.750	4.313
14	7.500	3.875	2.625	0.500	1.000	1.000	5.250
14A	7.500	3.125	2.625	0.500	1.000	0.750	5.250
15	10.00	4.250	3.688	0.500	1.000	1.000	3.875

CPLG SIZE	HP 1760 RPM	THRUST LBS.	A	C	D	E	F		G	H	CAPSCREWS		LENGTH	
							MIN.	MAX.			NO.	SIZE	STD	SPACER
3	125	20,000	2.000	1.500	4.313	0.500	0.938	1.250	2.500	4.250	4	0.375	5.500	9.813
7	300	30,000	2.688	1.500	4.313	0.625	1.188	1.750	2.875	5.000	6	0.375	6.875	11.188
10	700	75,000	2.688	2.250	4.313	0.750	1.438	2.250	3.625	6.000	6	0.500	7.625	11.938
11	900	85,000	3.000	2.500	5.250	0.750	1.938	2.625	4.250	6.875	6	0.625	8.500	13.750
12	900	85,000	3.000	2.500	5.250	0.750	1.938	2.625	4.250	6.875	6	0.625	8.500	13.750
13	1100	90,000	3.438	3.000	5.250	0.875	2.125	2.875	4.875	8.000	8	0.625	9.875	15.125
14	1500	100,000	4.375	3.500	5.250	1.000	3.000	3.875	6.250	9.750	8	0.750	12.250	17.500
14A	1500	100,000	4.375	3.500	5.250	1.000	1.938	3.875	6.250	9.750	8	0.750	12.250	17.500
15	2500	200,000	5.000	4.000	5.250	1.000	1.938	4.250	6.750	10.375	10	0.875	14.000	19.250

INFORMATION ABOVE REPRESENTS MINIMUM DIMENSIONS REQUIRED FOR COUPLING INSTALLATION  
 ALL TECHNICAL INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE