



# Istruzioni di lavoro

<b>Descrizione</b> Valori resistenze-assorbimenti motori 4-6"	<b>Istruzione num°:</b> 73 0014 001	<b>Data:</b> 02/12/2011
	<b>Revisione:</b> 01	<b>Pagina:</b> 1 di 2
	<b>Data di rev:</b>	<b>Rev. da:</b>
<b>Eseg. da:</b> De Bortoli Paolo	<b>Descrizione rev:</b>	

## Resistance 4" NBS4 values $\pm$ 5% (25 °C)

SINGLEPHASE 210/220/230 V - 50 Hz					
Type	kW	$\Omega$ (Main)	$\Omega$ (Start)	Watt 220V	Amps 220V
NBS4 050 M	0.37	6.50	14.8	400	2.5
NBS4 075 M	0.55	4.50	9.20	480	3.0
NBS4 100 M	0.75	3.55	7.60	550	3.8
NBS4 150 M	1.10	2.55	6.90	770	5.8
NBS4 200 M	1.50	2.00	4.90	990	6.6
NBS4 300 M	2.20	1.25	3.00	1100	7.8
NBS4K 400 M	3.00	0.90	2.00	1500	10.6
NBS4K 500 M	3.70	0.76	1.85	1800	14.5

SINGLEPHASE 230/240 V - 50 Hz					
Type	kW	$\Omega$ (Main)	$\Omega$ (Start)	Watt 240V	Amps 240V
NBS4 050 M	0.37	7.90	12.5	370	2.1
NBS4 075 M	0.55	4.10	6.30	400	2.7
NBS4 100 M	0.75	5.50	7.30	550	3.6
NBS4 150 M	1.10	3.00	5.50	720	6.2
NBS4 200 M	1.50	2.30	4.00	850	6.5
NBS4 300 M	2.20	1.50	2.45	1000	7.0
NBS4K 500 M	3.70	0.90	1.45	1450	13.5

THREE PHASE 380/415 V - 50 Hz				
Type	kW	$\Omega$	Watt 400V	Amps 400V
NBS4 050 T	0.37	54	320	1.05
NBS4 075 T	0.55	40	360	1.40
NBS4 100 T	0.75	26.4	320	1.65
NBS4 150 T	1.10	16.1	340	2.05
NBS4 200 T	1.50	12.3	480	3.25
NBS4 300 T	2.20	7.7	590	3.90
NBS4 400 T	3.00	5.5	780	5.90
NBS4 550 T	4.00	3.8	990	7.70
NBS4 750 T	5.50	3.0	1000	8.55
NBS4K 1000 T	7.50	2.2	1300	11.3



## Istruzioni di lavoro

<b>Descrizione</b> Valori resistenze-assorbimenti motori 4-6"	<b>Istruzione num°:</b> 73 0014 001	<b>Data:</b> 01/09/2008
	<b>Revisione:</b> 01	<b>Pagina:</b> 2 di 2
	<b>Data di rev:</b>	<b>Rev. da:</b>
<b>Eseg. da:</b> De Bortoli Paolo	<b>Descrizione rev:</b>	

### Resistance 6"NBS6 values $\pm$ 5% (25 °C)

THREE PHASE 380/415 V - 50 Hz D.O.L.				
Type	kW	$\Omega$	Watt 400V	Amps 400V
NBS6 550T	4.0	3.56	1450	5.6
NBS6 750T	5.5	2.32	1700	8.1
NBS6 1000T	7.5	1.90	1710	9.5
NBS6 1250T	9.2	1.30	2050	13.0
NBS6 1500T	11.0	0.81	2100	16.6
NBS6 2000T	15.0	0.68	2750	21.5
NBS6 2500T	18.5	0.52	3050	24.5
NBS6K 3000T	22.0	0.34	3000	37.5
NBS6K 4000T	30.0	0.35	3950	30.0

THREE PHASE 380/415 V - 50 Hz Star/Delta				
Type	kW	$\Omega$	Watt 400V	Amps 400V
NBS6 550T	4.0	5.40	1450	5.6
NBS6 750T	5.5	3.81	1700	8.1
NBS6 1000T	7.5	2.44	1710	9.5
NBS6 1250T	9.2	2.22	2050	13.0
NBS6 1500T	11.0	1.33	2100	16.6
NBS6 2000T	15.0	0.96	2750	21.5
NBS6 2500T	18.5	0.80	3050	24.5
NBS6K 3000T	22.0	0.52	3000	37.5
NBS6K 4000T	30.0	0.53	3950	30.0